

Pre-treatment of Ballast Water

FEATURES & BENEFITS

- Pre-treatment of ballast water when changing waters.
- Removal of Micro Organisms in ballast water.
- For use in Chemical Injection Ballast Water Treatment Systems.

DIRECTIONS FOR USE/APPLICATIONS & DOSAGE RATES

Dose according to manufacturer's recommendations.

SODIUM HYPOCHLORITE 12% SOLUTION

For advisory on Ballast Water Treatment please contact us at NAVADAN.
A range of test equipment is also available.



Product Information:
SODIUM HYPOCHLORITE 12% SOLUTION
www.navadan.com • +45 49 17 03 57 • navadan@navadan.com



Product Characteristics

SODIUM HYPOCHLORITE - 12% SOLUTION IS AVAILABLE in 200/208 ltr drums.

| | |
|----------------------|--|
| Appearance: | Yellow to green liquid |
| Specific gravity: | 1.24 |
| Flash Point: | None |
| pH-value (1% Sol.): | 11.5 – 12.5 |
| Odour: | Strong chlorine like |
| Solubility in water: | Completely soluble |
| Compatibility: | |
| Metals: | The concentrated product may react with aluminium, zinc, tin and their alloys. |
| Rubber: | None |

For Nature of special risks & safety regulations, please see our Material Safety Data Sheet



Product Information:
SODIUM HYPOCHLORITE 12% SOLUTION

www.navadan.com • +45 49 17 03 57 • navadan@navadan.com

