

SELF POWERED TELEPHONE SYSTEM (BATTERYLESS)

TELEPHONES

TYPE: SCM-MAG-A

MODEL: AU-MAG-A-24

(Telephone with amplifier)

SCM
SISTEMAS



FEATURES

- Excellent speech quality.
- 24 extensions selector switch.
- Built-in system amplifier w/capacitor battery.
- For instalation in wheelhouse and/or control room.
- Terminal for auxiliary 24 VDC power supply.
- Noise compensated microphone.
- Material: aluminium.
- Available headphone connection for noisy areas.
- Relay to activate additional devices incorporated in the circuit board.

TECHNICAL SPECIFICATIONS

Operating temperature	-20°C to +50°C
Acoustic alarm	80 dB(A) (1m)
Relative humidity	Up to 95% (non condensing)
Conversation time	20-30 min
Assembly	Bulkhead or console
Weight	Approx 2 kg
IP-rating	44
Resistive load	10A 250VAC / 30VDC
Inductive load	($\cos\phi = 0.4$; L/R = 7 ms) 5A250VAC / 30VDC

SELF POWERED TELEPHONE SYSTEM (BATTERYLESS)

TELEPHONES

TYPE: SCM-MAG-A

MODEL: AU-MAG-A-24

(Telephone with amplifier)

SCM
SISTEMAS

