

SELF POWERED TELEPHONE SYSTEM (BATTERYLESS)

TELEPHONES

TYPE: SCM-MAG-A

MODEL: AU-MAG-A-F-S

(Telephone with amplifier flush mounting type)

SCM
SISTEMAS



FEATURES

- Excellent speech quality.
- Single way.
- Built-in system amplifier w/capacitor battery.
- For instalation in wheelhouse and/or control room.
- Terminal for auxiliary 24 VDC power supply.
- Material: aluminium.
- Earpiece: ABS plastic.
Spiral cord (60 cm extensible to 1.5 m).

TECHNICAL SPECIFICATIONS

| | |
|-----------------------|---|
| Operating temperature | -20°C to +50°C |
| Acoustic alarm | 80 dB(A) (1m) |
| Relative humidity | Up to 95% (non condensing) |
| Conversation time | 20-30 min |
| Assembly | Flush mounting |
| Weight | Approx 2 kg |
| IP-rating | 44 |
| Resistive load | 10A 250VAC / 30VDC |
| Inductive load | (cosφ = 0.4; L/R = 7 ms) 5A250VAC / 30VDC |

SELF POWERED TELEPHONE SYSTEM (BATTERYLESS)

TELEPHONES

TYPE: SCM-MAG-A

MODEL: AU-MAG-A-F-S

(Telephone with amplifier flush mounting type)

SCM
SISTEMAS

