

SELF POWERED TELEPHONE SYSTEM (BATTERYLESS)

TELEPHONES

TYPE: SCM-MAG

MODEL: AU-MAG-A-S

(Telephone with amplifier single way)

SCM
SISTEMAS



FEATURES

- Excellent speech quality.
- For use on open air deck areas and bridge wings.
- Material: ABS plastic (fireproof).
- Earpiece: ABS plastic (fireproof).
Spiral cord (60 cm extensible to 1.5 m).
- Available headphone connection for noisy areas.
- Optional acoustic/luminous alarm via relay box.
- Relay incorporated.

TECHNICAL SPECIFICATIONS

Operating temperature	-20°C to +50°C
Acoustic alarm	80 dB (1m)
Relative humidity	Up to 95% (non condensing)
Conversation time	20-30 min
Assembly	Bulkhead or console
Weight	Approx 2 kg
IP-rating	54
Resistive load	10A 250VAC / 30VDC
Inductive load	($\cos\phi = 0.4$; L/R = 7 ms) 5A250VAC / 30VDC

SELF POWERED TELEPHONE SYSTEM (BATTERYLESS)

TELEPHONES

TYPE: SCM-MAG

MODEL: AU-MAG-A-S

(Telephone with amplifier single way)

SCM
SISTEMAS

