

## SELF POWERED TELEPHONE SYSTEM (BATTERYLESS)

### PORTABLES TELEPHONES

TYPE: SCM-MAG

**MODEL: AU-MAG-P-S-C**

**(Portable telephone single way with connector)**

**SCM**  
SISTEMAS



#### FEATURES

- Excellent speech quality.
- For use on open air desk areas and bridge wings.
- Material: ABS plastic (fireproof).
- Earpiece: ABS plastic (fireproof).  
Spiral cord (60 cm extensible to 1.5 m).
- Available headphone connection for noisy areas:  
Model: TA-ACM-A.
- Optional acousting/luminous alarm via relay box.
- Includes stuffing box for connection.

#### TECHNICAL SPECIFICATIONS

Operating temperature	-20°C to +50°C
Acoustic alarm	80 dB(A) (1m)
Relative humidity	Up to 95% (non condensing)
Assembly	Portable
Weight	Approx 2 kg
IP-rating	54
Resistive load	10A 250VAC / 30VDC
Inductive load	( $\cos\phi = 0.4$ ; L/R = 7 ms) 5A250VAC / 30VDC

# SELF POWERED TELEPHONE SYSTEM (BATTERYLESS)

PORTABLES TELEPHONES

TYPE: SCM-MAG

**MODEL: AU-MAG-P-S-C**

**(Portable telephone single way with connector)**

**SCM**  
SISTEMAS

