

# SELF POWERED TELEPHONE SYSTEM (BATTERYLESS)

## TELEPHONES

TYPE: SCM-MAG

**MODEL: AU-MAG-S**  
(Telephone single way)

**SCM**  
SISTEMAS



### FEATURES

- Excellent speech quality.
- For use on open air deck areas and bridge wings.
- Material: ABS plastic (fireproof).
- Earpiece: ABS plastic (fireproof).  
Spiral cord (60 cm extensible to 1.5 m).
- Available headphone connection for noisy areas.
- Optional acoustic/luminous alarm via relay box.
- Relay incorporated.

### TECHNICAL SPECIFICATIONS

Operating temperature	-20°C to +50°C
Acoustic alarm	80 dB (1m)
Relative humidity	Up to 95% (non condensing)
Conversation time	20-30 min
Assembly	Bulkhead or console
Weight	Approx 2 kg
IP-rating	54
Resistive load	10A 250VAC / 30VDC
Inductive load	( $\cos\phi = 0.4$ ; L/R = 7 ms) 5A250VAC / 30VDC

## SELF POWERED TELEPHONE SYSTEM (BATTERYLESS)

TELEPHONES

TYPE: SCM-MAG

**MODEL: AU-MAG-S**  
(Telephone single way)

**SCM**  
SISTEMAS

