

SOUND POWERED TELEPHONE SYSTEMS

TELEPHONES

TYPE: SCM-TA

MODEL: TA-4CI-C

(Telephone with connector for headset)

SCM
SISTEMAS



FEATURES

- Sound powered telephone with socket for headsets.
- Excellent speech quality.
- 12 extensions selector switch.
- For use on open air desk areas and bridge wings.
- Material: ABS plastic (fireproof).
- Earpiece: ABS plastic (fireproof).
Spiral cord (60 cm extensible to 1.5 m).
- Available headphone connection for noisy areas:
Model: TA-ACM-A.
- Optional acousting/luminous alarm via relay box.
- Includes cableglands for connection.

TECHNICAL SPECIFICATIONS

Operating temperature	-20°C to +50°C
Acoustic alarm	80 dB(A) (1m)
Relative humidity	Up to 95% (non condensing)
Assembly	Bulkhead or console
Weight	Approx 2 kg
IP-rating	54
Resistive load	10A 250VAC / 30VDC
Inductive load	($\cos\phi = 0.4$; L/R = 7 ms) 5A250VAC / 30VDC

SOUND POWERED TELEPHONE SYSTEMS

TELEPHONES

TYPE: SCM-TA

MODEL: TA-4CI-C

(Telephone with connector for headset)

SCM
SISTEMAS

