

# SOUND POWERED TELEPHONE SYSTEMS

## TELEPHONES

TYPE: SCM-TA

**MODEL: TA-4CI-MG-B**

**(Telephone + watertight box with shock and vibration isolation)**

**SCM**  
SISTEMAS



### FEATURES

- Excellent speech quality.
- 12 extensions selector switch.
- Suitable for high-noise level areas.
- Waterproof housing.
- Material: GW plastic 120° (RAL 7035).
- Earpiece: ABS plastic (fireproof).  
Spiral cord (60 cm extensible to 1.5 m).
- Available headphone connection for noisy areas:  
Model: TA-ACM-A.
- Includes dampers (VIBCABLE V3CA8010 series).
  - Damping up to 40%.
  - High deflection in all directions.
  - Natural frequency between 5 Hz and 25 Hz.
  - Compliant with MIL-STD-167.

### TECHNICAL SPECIFICATIONS

Operating temperature	-20°C to +50°C
Relative humidity	Up to 95% (non condensing)
Assembly	Bulkhead
Weight	Approx 6 kg
IP-rating	66
Resistive load	10A 250VAC / 30VDC
Inductive load	( $\cos\phi = 0.4$ ; L/R = 7 ms) 5A250VAC / 30VDC

# SOUND POWERED TELEPHONE SYSTEMS

TELEPHONES

TYPE: SCM-TA

**MODEL: TA-4CI-MG-B**

**(Telephone + watertight box with shock and vibration isolation)**

**SCM**  
SISTEMAS

