

SOUND POWERED TELEPHONE SYSTEMS

TELEPHONES

TYPE: SCM-TA

MODEL: TA-4CI-MG-S-B

(Telephone + watertight box with shock and vibration isolation)

SCM
SISTEMAS



FEATURES

- Excellent speech quality.
- Suitable for high-noise level areas.
- Waterproof housing.
- Material: GW plastic 120° (RAL 7035).
- Earpiece: ABS plastic (fireproof).
Spiral cord (60 cm extensible to 1.5 m).
- Available headphone connection for noisy areas:
Model: TA-ACM-A.
- Includes dampers (VIBCABLE V3CA8010 series).
 - Damping up to 40%.
 - High deflection in all directions.
 - Natural frequency between 5 Hz and 25 Hz.
 - Compliant with MIL-STD-167.

TECHNICAL SPECIFICATIONS

Operating temperature	-20°C to +50°C
Relative humidity	Up to 95% (non condensing)
Assembly	Bulkhead
Weight	Approx 6 kg
IP-rating	66
Resistive load	10A 250VAC / 30VDC
Inductive load	($\cos\phi = 0.4$; L/R = 7 ms) 5A250VAC / 30VDC

SOUND POWERED TELEPHONE SYSTEMS

TELEPHONES

TYPE: SCM-TA

MODEL: TA-4CI-MG-S-B

(Telephone + watertight box with shock and vibration isolation)

SCM
SISTEMAS

