

# )

# MAXI-VAP PLUS 25 LTR

Product group: 654 Product number: 777707

NALFLEET<sup>TM</sup> Maxi-Vap Plus is a concentrated solution of an organic poly-electrolytes specifically developed for the control of scale deposition in sea water evaporators. It is miscible with water in all proportions.

# **Product information**

This product supersedes product no: 777187

# Features

- Maintains design output and efficiency of evaporators for extended periods
- Improves distillate quality by controlling foaming and carry over

# Benefits

- Reduces downtime and maintenance costs
- Economical in use

# Specification

# General

Invent Hazard Material (IMO/EU) classification	C-11
--	------

# 

# **Physical properties**

Density [g/ml]	1.026 - 1.066
Form	Liquid
Materials compatibility	Polypropylene, Polyethylene, PVC, Butyl Rubber, Nitrile Rubber, EPDM, Viton, Stainless Steel, Nickel, Mild Steel
рН	9.0 - 10.0

#### **Technical data**

Not Compatible

Aluminium, Zinc

# **Approvals**

Approved by the UK Department of Trade Marine Safety Agency.

# Documents

SDoC and MD for IHM

# **Directions for use**

Although best results will be obtained by starting the treatment with a clean evaporator, NALFLEET™ Maxi-Vap Plus Liquid will improve performance of an evaporator which has not been de-scaled.

#### **Dosing Method**

The daily requirement of NALFLEET™ Maxi-Vap Plus should be mixed with evaporated water or condensate and diluted to the

normal working level of the mixing tank. The solution can then be applied continuously via a flow meter to the evaporator shell or into the salt water feed line to the evaporator.

### **Dosing and Control**

The flow rate should be adjusted to empty the tank over a 24 hour period. WSS can supply a suitable dosing tank and pump for this purpose. The Marine Safety Agency of the Department of Trade and Industry has agreed that NALFLEET<sup>M</sup> Maxi-Vap Plus Liquid can be used as a scale inhibitor in the feed water evaporators producing fresh water for drinking and culinary purposes. Typical dose rate is 10mls per ton of evaporator output.

# **Related products**

#### Accessories

656207/APORATOR DOSING UNIT ON GRAVITY

# Is accessory to

777336UAGUARD	777332 UAGUARD
CW DOSING	BW 2 PUMP
SYSTEM	DOSING
	SYSTEM

#### Consumables

778419 TABLE WATER TEST KIT

### Is frequently bought together with

571396COR NB LIQUID 25 LTR	735977AR-71 BIOCIDE 3X5L NOT IN USA&CAN
680843 AL 25 LTR	<b>698720</b> TOTREAT - 25 LTR
<b>698702</b> YGEN SCAVENGER PLUS 25 LTR	7777100LFLEET 2000 25 LTR

#### This page is printed from:

https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/water-treatment-chemicals/water-production-treatment/maxi-vap-plus-25-ltr/