

4000200300

P-6211

Industrial Telephone



DESCRIPTION

- Integrated loudspeaker/microphone
- Handset, 2 meter sturdy curled cord
- Hands-free, duplex communication
- 2" Graphic backlit display:
 - Menus and navigation wheel/key
 - Contact list
 - Caller ID
- Dimmable backlight (keypad)
- Privacy switch (Do not disturb) with priority override
- Manual PTT (push-to-talk) key
- 3 pcs programmable direct access keys (A-B-C)
- Volume adjustment with override
- Speakerphone SPL level >85dB(A) (integrated loudspeaker)
- Bulkhead mounted
- MMI according to IEC 62288 Ed 2.0
- Status/health indicator
- Multiple ring melodies
- Integrated call relay for external signal device
- Output to external loudspeaker, 8 W; SPL level > 110dB (loudspeaker dependent)
- Headset connection
- Complies with IEC 60945 Standard for Marine Equipment
- DNV/ABS/RMRS/CCS type approval and compatible with NORSOK

The P-6211 is equipped with an amplifier for additional external loudspeaker and relay for external call signal devices (beacon, siren, etc.). The unit is bulkhead mounted.

Created: 10.12.2019, updated: 08.05.2020

page 1/3

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel - All rights reserved.

SPECIFICATIONS

MECHANICAL

Dimensions (WxHxD)	144 x 216 x 120 mm
Weight	1.1 kg
Material	Plastic (PC/ASA)
Color	Grey – RAL 7021/7043
Mounting	Bulkhead / Direct or Bracket
Fixing	4 x M4 bolts
Access	Front
Cable Entry	Side / Bottom – through Glands (optional)
Connector Type	RJ45

[Export Table Data](#)

ELECTRICAL

Power Supply	System / Line feed (Basic telephone operation). Additional 24V/1.5A input for call relay and amplifier for external loudspeaker.
Line Format	UpN (Digital 2Wire – 2B+D)
Power Consumption	10W (max – external loudspeaker)
Termination	Line: RJ45, two center cores. External loudspeaker/external signal device, etc: clamp terminals.
Compass Safe Distance	>5 m
External loudspeaker	8W / 20Ω
External signal device, Call relay	6.3A (max)

[Export Table Data](#)

ENVIRONMENTAL

Temperature	-25°C to +55°C
Humidity	+93% (at +40°C)
Ingress Protection Rating	IP-56 (exposed)
UL94	V0

[Export Table Data](#)

TECHNICAL DIMENSIONS

